

TDM-P150SH5TAGF-D39

15" Military P-cap Monitor, 1500nits, Rackmount, Certificated with MIL-STD-461G, Front Side IP65, AG, Panel Mounting Kits, 9~36VDC Power Input



Features

- ▶ 15" 1024*768 LCD and P-cap Touch
- ▶ IP65 and Rackmount Shape Front Bezel
- ▶ 1500 nits LED backlight
- ▶ Mosmite Film with AR feature
- ▶ Anti-Glare
- ▶ HDMI by Metal Circular Connector
- ▶ USB fo Touch by Metal Circular Connector
- ▶ DC Power Input by MS3114E8 Circular Connector
- ▶ DC 9~36V Power Input with 90W power adapter
- ▶ -40~70°C Operating Temperature

I/O Connect

External I/O Port	HDMI by Metal Circular Connector (with 1.5 meter external cable) USB(for Touch) by Metal Circular Connector (with 1.5 meter external cable) Power Input by MS3114E8 Connector
-------------------	---

LCD

Max. Resolution	1024*768
Contrast Ratio	700 : 1
Max. Color	16.2M
Luminance	1500 nits
View Angle	80/80/70/70

Power Requirement

Power Input	9~36VDC Power Input by MS3114E8 Connector
-------------	---

Touch Screen

Type	P-cap USB
------	-----------


Environment

Operating Temp	-40~70 °C · IEC-60068-2-1/2/14
Storage Temp	-40~70 °C
Humidity	10~90% @40 °C, non-condensing
EMC	MIL-STD-461G Certification FCC / CE Class A Certification
Vibration	MIL-STD-810H, Method 514.8, Procedure I, 5~500Hz (Certification)
Shock	MIL-STD-810H, Method 516.8, Procedure I, 20g 11ms (Certification)

Mechanical

Construction	Aluminum Bezel and Metal case
IP Rating	IP65 Front Side
Mounting	Wall Mount , VESA Mount
Dimension	TBC

Dimension & I/O Connector



Optional Front Side OSD Buttons



Ordering Information

TDM-P150SH5TAGF-D39	15" Military P-cap Monitor, 1500nits, Rackmount, Certificated with MIL-STD-461G, Front Side IP65, AG, Panel Mounting Kits, 9~36VDC Power Input
---------------------	--